



de Trans / WK Trans

Evaluation unit

The Data Transfer Units allows data collectors to be downloaded to a PC via a serial interface. The process is without electrical contact ensuring that it is very reliable.

If data collector and evaluation PC are based at different locations, data can be remotely transferred via modem. This operation is accomplished by programming the desired telephone number into the data transfer unit. Once the data collector is placed in the transfer unit and communication is established, data transfer, collector initialisation and clock synchronisation take place automatically. The data can be transferred via landline or GSM data transfer.

The Transfer Unit de Trans is compatible with duostar and all de series data collector.

Your benefits at a glance:

- Simple operation
- Remote data transmission possible
- Can be used with standard and GSM modems and GSM phones
- No wear and tear due to contactless reading



Technical Data

Dimensions (W x H x D):	130 x 60 x 200 mm
Housing:	ABS plastic
Power supply:	12V / 640 mA
Interface:	RS232

Accessories

Serial cable for PC or modem
 Wall plug supply 12V / 640 mA
 USB-Adapter SNG0
 Data-Switch for the parallel use of two data transfer units on one PC interface

Suitable Data Collectors

de Trans:	Duostar and the previous types de prox, de watch
WK Trans:	magprox and the previous types mag II, mag III, magscan, proxscan, triscan, WK 1000, WK 1100

Suitable Software

The data transfer units are compatible with all dataLog®-software packages.